



## VScom USB-2COMi-M

USB to 2 RS422/485 ports adapter



### KEY FEATURES

- DIN-Rail mountable
- 2 x RS422/485 ports
- Terminal block
- Speed up to 921.6kbps
- No external power supply
- Metal case

### Overview

Serial ports on USB allow further use of existing devices, even when the computer doesn't offer serial ports.

The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.



### Specifications

Serial interface	RS422/485 port
Ports	2
Speed	Up to 921.6kbps
RS422/485 signals	RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND
Power	USB Bus powered, no external power supply
Driver	Windows 98, ME, 2000, XP, 2003 Server, Vista Linux (Kernel 2.4 and up built-in)
Connectors	2 DB9 male and terminal block
Dimensions	115 x 84 x 25 mm (W×L×H) 137 x 84 x 25 mm with DB9 connector and ears

### Ordering Information

Art. No	643
Product Name	VScom USB-2COMi-M
Packing List	VScom USB-2COMi-M, USB cable 0,9m, CD, English Documentation
Optional Accessories	DK 35A - DIN-Rail mounting kit