

# USB-32COM-RM

## USB to 32 RS232 ports Adapter

Hardware Specifications	
Serial Interface	32 x RS232 Connector 8 x 4 RJ45, adapter to DB9 male included
Speed	Up to 500 kbps
Signals	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
USB Interface	Self powered Built-in power supply 110-240V AC 47-63 Hz, 25VA
Driver	Windows 2000 to Windows 8 (x86 and x64) Windows Server 2000 to 2008 R2 (x86 and x64) Linux (Kernel 2.6 built-in, 2.4 available)
Dimensions	429 x 147 x 44 mm <sup>3</sup> ( W x L x H ) 451 x 147 x 44 mm <sup>3</sup> with DIN Rail ears
Approvals	
EMC	FCC Class A, CE Class A
Environment	RoHS
Ordering Information	
Art. No.	651
Product Name	VScom USB-32COM-RM
Packing list	<ul style="list-style-type: none"><li>◆ VScom USB-32COM-RM Adapter</li><li>◆ USB cable 0,9m</li><li>◆ Serial Adapter cables</li><li>◆ Power cord</li></ul>
Optional Accessories	9PF-9PF (Art No. 661) - RS232 Null-Modem adapter, change male to female

## Overview

Serial ports on USB allow further use of existing devices, even when the computer doesn't offer serial ports.

The high speed serial port with the 2 Kbyte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.

©2013, VSCOM. The VSCOM logo is a trademark of VS Vision Systems GmbH. Other products and brand names mentioned herein may be trademarks or registered trademarks of their respective owners. The information contained herein is subject to change without notice.

You can purchase VSCOM's products easily from a wide variety of leading technology distributors or partners. Please contact us to find the best ordering method for your needs.

## Connect to Success

USB-32COM-RM (Art No. 651)  
sales contact : [sales@vsc.com.de](mailto:sales@vsc.com.de)

Datasheet Ver. : 651 PDF062013V01