

VScom USB-16COM-M CBL

USB to 16 RS232 Ports Adapter

Hardware Specifications	
Serial Interface	16 x RS232 Connector 2 x DB62 female, Adapters available Speed up to 500 kbps Signals Tx/D, Rx/D, RTS, CTS, DTR, DSR, DCD, GND
USB Interface	USB 2.0 <ul style="list-style-type: none">Self poweredExternal power supply 9-35V DCConnected by terminal blockAdapter 12V included
Driver	Windows 2000 to Windows 8 (x86 and x64) Windows Server 2000 to 2008 R2 (x86 and x64) Linux (Kernel 2.6 built-in, 2.4 available)
Dimensions	124 x 78 x 51 mm ³ (W x D x H)
Approvals	
EMC Environment	FCC Class A, CE Class A RoHS
Ordering Information	
Art. No.	653
Product Name	VScom USB-16COM-M CBL
Packing list	<ul style="list-style-type: none">VScom USB-16COM-M CBL AdapterUSB cable 0,9mPower adapter
Optional Accessories	<ul style="list-style-type: none">DK 35A (Art No. 662) - DIN-Rail mounting kitDB62 to ... Octopus cables and connection box

Overview

Serial ports on USB allow further use of existing devices, even when the computer doesn't offer serial ports.

The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.

USB-16COM-M CBL uses a small case due to the high-density DB62 combi connectors for the serial ports. Mounted even in narrow environment, it connects to serial devices via an octopus cables or connection boxes.

©2013, VSCOM. The VSCOM logo is a trademark of VS Vision Systems GmbH. Other products and brand names mentioned herein may be trademarks or registered trademarks of their respective owners. The information contained herein is subject to change without notice.

You can purchase VSCOM's products easily from a wide variety of leading technology distributors or partners. Please contact us to find the best ordering method for your needs.

Connect to Success